



FULLY GLAZED DOOR – PARTIALLY INSULATED (EW120/EI30)

DESCRIPTION

Special designed fully glazed fire rated door & partition for Lift Lobby, Corridor, Entrance door in Narrow stiles and rails with special concealed hardware for good aesthetic view, increased glazed area, slimmer profile having integrity & insulation application with special fire resistive infill for EI system.

SPECIFICATIONS

Construction	Insulated special mechanically formed narrow profile
Materials	Galvanised steel sheet conform to IS or equivalent standard
Thickness	60mm thick door with sheet thickness 1.6mm
Insulation	Mineral wool 96 kg/m ³
Application	Lift Lobby, corridor, entry door
Frame Section	35 mm x 60 mm (Vertical side) & 60 mm x 60 mm (Horizontal side)
Ironmongery	Fire Rated Ironmongery
Fire Rated Glass	15mm thickness - Contraflam lite plus / 14 mm thick Contraflam lite inter-layered FR Glass with UV stability & Durability offer 120 minutes fire rating with framing
Test Standard	IS:16947:2018
Test Lab	NABL Accredited
Finish	Powder Coated / Wooden Finish (ON REQUEST)

ADDITIONAL FEATURES

- ✓ Lock seam joints Knock down frame, fitted with fire
- ✓ seal & smoke seal Fire rating as per IS:16947-2018

FULLY GLAZED DOOR - PARTIALLY INSULATED (EI20 I30)

