



## FULLY GLAZED SINGLE/DOUBLE LEAF DOOR SET (EW120 & EI20) DSR STANDARD

### DESCRIPTION

Navair offer special designed fully glazed fire rated door & partition for Lift Lobby, Corridor, Entrance door, Shop front in Narrow stiles and rails with special concealed hardware for good aesthetic view, increased glazed area, slimmer profile having integrity & radiation control, fitted with interlayered specially designed Fire Rated glass to achieve min. 20 min partial insulated properties.

### SPECIFICATIONS

Construction	Specially designed slimmer framing to meet the Requirement
Materials	Galvanised steel sheet confirm to IS 277
Thickness	60mm thick door with sheet thickness 1.6mm
Core infill	Mineral wool 96 kg/m <sup>3</sup>
Application	Lift Lobby, corridor, entry door
Frame Section	As per DSR (35 mm x 60 mm (Vertical side) & 60 mm x 60 mm (Horizontal side)
Ironmongery	Fire Rated Ironmongery
Test Lab	IFC Exova Warrington & Spectro NABL LAB
Standard	BS 476 Part 20 & 22
Fire Rated Glass (EW 120 I20)	Fitted with inter layered FR glass to provide 120 minutes fire rating 120 minutes radiation control with 20 minutes insulation properties of Saint Gobain make
Finish Fire	Powder Coated
Rating	120 minutes

### ADDITIONAL FEATURES

- ✓ Lock seam joints Knock down
- ✓ frame Fire rating as per Bs476 Part
- ✓ 20&22

## FULLY GLAZED SINGLE/DOUBLE LEAF DOOR SET DSR SPECIFICATIONS

